



American Made  
Ergonomically Designed

# Give your *Bass Boat* a comfortable deck!



## PRO-TECH DECK

Marine Carpet Padding



Standard thickness: 1/4"

Custom thicknesses  
are also available

Standard roll sizes:  
36" and 42" widths,  
Rolls come in 50' lengths

Custom widths and  
lengths are also available



Specially designed Marine Carpet Padding is unlike any other padding.  
This material is made from the World's #1 Anti-Fatigue Mat material!

### Pro-Tech Ergonomic Casting Deck

#### *Features:*

- Re-bond from virgin nitrile Ortho anti-fatigue mat scraps.
- Can be made into any size or shape.
- Closed cell material is designed to get wet. The compound is formulated with anti-microbial to eliminate mold, mildew, and bacteria.

#### *Benefits:*

- Fish in total comfort.
- Excellent compression deflection for maximum anti-fatigue values while standing.
- Don't spook the fish—reduces sound and vibrations on boat deck.
- Enhances carpet beauty and extends carpet life.
- No net rule, no problem—give the fish a soft place to land.
- Great for kneeling down to grab a fish.
- Adds floatation to boats.
- Reduces condensation under deck lids.

### Go Green!

Keeping scrap  
material out of  
landfills while saving  
natural gas,  
electricity, and  
petroleum by recycling



# *Marine Carpet Padding*

**Designed for new boat manufacturing or re-carpeting**

How is the Pro-Tech Deck installed?

- *Simply cut to fit with scissors or a razor blade. Glue material to the boat deck and then glue carpet to the material. Stop material 1/2" short of all edges, this will allow the carpet to taper down to deck.*

What kind of adhesive should be used?

- *It is very important to use the correct adhesive. Remember this marine carpet padding is closed cell material and no air can pass through material to dry adhesive. It is recommended to use adhesive made by Bird Song Adhesive. To purchase or for additional information contact:*



Recommended Adhesive Product #: BSA173

Contact—Flammable, HAPs Free

Bird Song Adhesives, Inc.

615-860-2798

Contact: Greg Rogers

## ***Specifications:***

- Maximum temperature material will withstand without defects 200°, lowest temperature - 5° (tested and approved)
- Water/Fluid Absorption: 24 hour free stand water test — PASSED
- Anti-microbial additive to prevent mold, mildew and bacteria: Dovicide by Dow Chemical added to compound—MSDS available
- Chemical and petroleum product resistance — EXCELLENT
- Compression Deflection — EXCELLENT—test results available

Why? *This is a pressure cured molded material (not inexpensive extruded material)*

---

## **Pro-Tech Deck Pricing**

**36" width**

**42" width**

**1/4" \$5.94 per ft. (2.00 lbs. per ft)**

**\$7.14 per ft. (2.70 lbs. per ft.)**

Wholesale prices available

***\* Available in 50' standard roll lengths \****

Custom size or shape needed? Fax your drawing with measurements to Pro-Tech Marine Rubber, Inc. at 760-343-3667 or call 1-800-317-8516